

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

**(19) World Intellectual Property Organization
International Bureau**



1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1

(43) International Publication Date
1 March 2001 (01.03.2001)

(10) International Publication Number
WO 01/13844 A1

PCT

(51) International Patent Classification⁷: A61F 13/15 (74) Agents: CONNELLY, Thomas, J. et al.; Kimberly-Clark Worldwide, Inc., 401 N. Lake Street, Neenah, WI 54956 (US).

(21) International Application Number: PCT/US00/23077

(22) International Filing Date: 23 August 2000 (23.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/150,329 23 August 1999 (23.08.1999) US
09/637,429 11 August 2000 (11.08.2000) US

(71) Applicant: KIMBERLY-CLARK WORLDWIDE, INC. [US/US]; 401 N. Lake Street, Neenah, WI 54956 (US).

(72) Inventors: BRUEMMER-PRESTLEY, Mary, Anne; 418 East Pershing Street, Appleton, WI 54911 (US). SCHMOKER, Suzanne, Marie; 4212 Brooks Road, Oshkosh, WI 54904 (US). BORDAIN, Nefetari, Edris; 5508 Treelodge Parkway, Dunwoody, GA 30350 (US). FREIBURGER, Sarah Jane, Marie; 2708 Welhouse Drive, Kaukauna, WI 54130 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— With international search report.


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: REFASTENABLE ABSORBENT ARTICLE



(57) Abstract: An absorbent article is disclosed having a refastenable mechanism. The absorbent article has a front portion, a back portion and a crotch portion. The crotch portion connects the front portion to the back portion. The front portion has a first end, a second end, a first side edge and a second side edge. First and second lateral sections are releasably attached to the front portion and each of the first and second lateral sections has an outer edge. The back portion has first and second side edges and first and second ends. The back portion is divided into a first section and a second section. The first section has a length L_2 measured perpendicularly from the first end of the back portion to a line drawn parallel thereto. The second section has a length L_1 measured perpendicularly from the second end of the back portion to the line drawn parallel to the first end whereby a ratio L_2/L_1 is established which ranges from between about 0.1 to about 2. The absorbent article further includes an absorbent secured to at least one of the front, back or crotch portions. Each of the outer edges of the first and second lateral sections are secured to one of the first and second side edges of the back portion to form a pant-like article having a waist opening and a pair of leg openings.

WO 01/13844 A1

REFASTENABLE ABSORBENT ARTICLE

FIELD OF THE INVENTION

5 This invention relates to an absorbent article having a refastenable mechanism. More specifically, this invention relates to a disposable absorbent article having a refastenable mechanism that improves body fit and reduces the likelihood of fluid leakage.

BACKGROUND OF THE INVENTION

10 Today, various disposable absorbent articles exist which are designed to absorb and retain body fluid and/or excrement. Examples of such articles include incontinence products such as pants, briefs and undergarments, baby diapers, feminine care menstrual pants, training pants, etc. While most of these articles perform satisfactorily for their
15 intended purpose, some are difficult to remove from the body of the wearer. Many do not have a refastenable mechanism that allows the article to be easily adjusted during use or be easily removed from the wearer's body before the product is permanently discarded while maintaining an underwear like fit. Some of today's commercially available products do not conform well to the human body and this poor fit increases the likelihood of fluid
20 leakage while the product is being worn. Therefore, there remains a need for a disposable absorbent article having a refastenable mechanism that will provide improved fit to the human body and reduce the likelihood of fluid leakage.

 Now, an absorbent article has been invented which has a refastenable mechanism that improves body fit and reduces the likelihood of fluid leakage.

25

SUMMARY OF THE INVENTION

 Briefly, this invention relates to an absorbent article having a refastenable mechanism. The absorbent article has a front portion, a back portion and a crotch portion.
30 The crotch portion connects the front portion to the back portion. The front portion has a first end, a second end, a first side edge and a second side edge. First and second lateral sections are releasably attached to the front portion and each of the first and second lateral sections has an outer edge. The back portion has first and second side edges and first and second ends. The back portion is divided into a first section and a
35 second section. The first section has a length L_2 measured perpendicularly from the first

end of the back portion to a line drawn parallel thereto. The second section has a length L_3 measured perpendicularly from the second end of the back portion to the line drawn parallel to the first end whereby a ratio L_2/L_3 is established which ranges from between about 0.1 to about 2. The absorbent article further includes an absorbent secured to at least one of the front, back or crotch portions. Each of the outer edges of the first and second lateral sections are secured to one of the first and second side edges of the back portion to form a pant-like article having a waist opening and a pair of leg openings.

The general object of this invention is to provide an absorbent article having a refastenable mechanism. A more specific object of this invention is to provide a disposable absorbent article having a refastenable mechanism that improves body fit and reduces the likelihood of fluid leakage.

Another object of this invention is to provide an absorbent article having a refastenable mechanism that is easy to manufacture, is relatively inexpensive and is easy to use.

A further object of this invention is to provide an absorbent article having a refastenable mechanism that provides the wearer with a choice of how to apply and/or remove the absorbent article, i.e. pull the article up around the wearer's torso versus refasten the article around the wearer's torso.

Still another object of this invention is to provide an absorbent article that can easily be adjusted to conform to a wearer's body.

Other objects and advantages of the present invention will become more apparent to those skilled in the art in view of the following description and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top plane view of an absorbent article having a refastenable mechanism and shown in a pre-assembled flat configuration.

Fig. 2 is a cross-sectional view of Figure 1 taken along line 2—2.

Fig. 3 is a cross-sectional view of Figure 1 taken along the line 3—3.

Fig. 4 is a cross-sectional view of Figure 1 taken along the line 4—4.

Fig. 5 is a top view of an alternative absorbent assembly.

Fig. 6 is a cross-sectional view of Fig. 5 taken along line 6—6.

Fig. 7 is a perspective view of the "in use" configuration of the absorbent article shown in Figure 1 once the first and second lateral section and the back portion are secured together.

Fig. 8 is a top view of the back portion of the absorbent article with the elastic removed for clarity and showing one way to measure a ratio A_1/A_2 for the second section in order to obtain improved body fit.

Fig. 9 is a top view of the back portion and crotch portion of the absorbent article with the elastic removed for clarity and showing an alternative way to measure a ratio A_3/A_4 for the second section in order to obtain improved body fit.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figs. 1 to 4, an absorbent article 10 having a refastenable mechanism is shown. The absorbent article 10 is preferably a disposable article having a longitudinal central axis X—X, a transverse central axis Y—Y and a vertical central axis Z—Z. The absorbent article 10 includes a front portion 12, a back portion 14 and a crotch portion 16. The crotch portion 16 connects the front portion 12 to the back portion 14. The front, back and crotch portions 12, 14 and 16 can be formed from a single piece of material or from two or more pieces of material. Each of the front, back and crotch portions 12, 14 and 16 can be a single layer of material or each can be formed as a laminate having two or more layers. In Fig. 2, the front portion 12 is shown as a single layer 18 although it could be formed from a laminate. In Figs. 3 and 4, the back portion 14 and the crotch portion 16 are shown as a laminate 20 having an upper layer 22 and a lower layer 24. Preferably, the front, back and crotch portions 12, 14 and 16, respectively, are formed as a laminate having two layers.

When a laminate 20 is utilized, the upper layer 22 faces toward the body of the wearer in use and can be either liquid permeable or liquid-impermeable. A thermoplastic film can be used to make the upper layer 22 liquid-impermeable. The lower layer 24 faces away from the body of the wearer in use and it too can either be liquid permeable or liquid-impermeable. Preferably, the lower layer 24 is liquid permeable and is formed from a soft material such as a non-woven. Spunbond is a non-woven material manufactured by Kimberly-Clark Corporation that is soft and pliable and functions well as the lower layer 24. It is beneficial to make one of the layers 22 or 24 liquid-impermeable in the crotch portion 16 so as to prevent body fluid absorbed by the absorbent article 10 from exiting.

The front portion 12, which will be aligned around a portion of the front torso of a wearer's body in use, includes a first end 26, a second end 28, a first side edge 30 and a second side edge 32. First and second lateral sections 34 and 36, respectively, are releasably attached to the front portion 12. This provides a refastenable mechanism that

can be released and then refastened and adjusted as many times as needed by the wearer. Each of the first and second lateral sections 34 and 36 has an inner edge 38 and 40, respectively, and an outer edge 42 and 44, respectively. The inner edges 38 and 40 can be arranged parallel to the longitudinal central axis X—X of the absorbent article 10.

5 Preferably, the inner edges 38 and 40 are aligned adjacent to one another. More preferably, the inner edges 38 and 40 are arranged in an abutting relationship to one another. The inner edges 38 and 40 can initially be directly or indirectly attached to one another if desired. For purposes of manufacturing, it is sometimes advantageous to secure different members to one another so as to facilitate high-speed production.

10 One means of attaching the inner edges 38 and 40 of the first and second lateral sections 34 and 36, is to form breakable bonds or perforations 46 therebetween. For example, a line of perforations 46 or a line of frangible bonds 46 can join the two inner edges 38 and 40 together. The perforations or frangible bonds 46 should be designed so that they can be easily broken by the wearer. The perforations or frangible bonds 46 can
15 be initially broken before the absorbent article 10 is placed around the torso of the user or after the absorbent article 10 has been worn but just before an adjustment is required to improve body fit.

Each of the first and second lateral sections 34 and 36 can be formed from a single layer of material or be formed as a laminate. When the first and second lateral
20 sections 34 and 36 are in the form of a laminate, they should have an upper layer 48 and a lower layer 50. The first and second lateral sections 34 and 36 can be either liquid permeable or liquid-impermeable. Preferably, the first and second lateral sections 34 and 36 are liquid permeable and are constructed from a soft material such as a non-woven. The first and second lateral sections 34 and 36 can be formed from an elastic material or
25 contain multiple elastic strands 52, as shown in Figs. 1 and 2. The elastic strands 52 can vary in size, length and shape. Elongated elastic ribbons, elastic strips, elastic bands, elastic tape having round, flat or some other cross-sectional configuration can also be used.

It should be noted that the elastic 52 would provide the first and second lateral
30 sections 34 and 36 with extendible properties. Alternatively, the first and second lateral sections 34 and 36 can be formed from a material that exhibits elastomeric properties. The elastic 52 can be formed from rubber, polyurethane or other elastomeric materials. A suitable material is LYCRA® that is commercially available from the E.I. Du Pont De Nemours and Company. LYCRA® is a trademark of E.I. Du Pont De Nemours and
35 Company having an office in Wilmington, Delaware.

The elastic 52 can include two or more members positioned between the upper and lower layers 48 and 50, respectively, and held in place by glue, an adhesive or some other type of binder. Preferably, the elastic 52 is in the form of multiple strands arranged in parallel rows relative to one another. Other arrangements for the elastic 52 can also be used.

Turning our attention to Fig. 2, one can clearly see that the first and second lateral sections 34 and 36 overlay a substantial amount of the front portion 12. The first and second lateral sections 34 and 36 could overlay the entire surface area of the front portion 12 if desired. The first and second lateral sections 34 and 36 are releasably attached to the front portion 12 by a fastener 54. In Fig. 2, the fastener 54 is shown as a hook and loop fastener having a hook component 56 and a loop component 58. Either the hook component 56 or the loop component 58 can be secured to the front portion 12 or to the first and second lateral sections 34 and 36. It should also be recognized that other types of fasteners could be used to releasably attach the first and second lateral sections 34 and 36 to the front portion 12. Such other fasteners can include adhesives, co-adhesives, as well as mechanical fasteners, such as buttons and corresponding buttonholes, etc. Other fasteners are known to those skilled in the art.

The front portion 12 can be constructed from a material that has hook or loop properties or have a separate piece of hook or loop material secured thereto to give it the ability to fasten onto the first and second lateral sections 34 and 36. Likewise, the first and second lateral sections 34 and 36 can be constructed from a material that has hook or loop properties or have a separate piece of hook or loop material secured thereto to give it the ability to fasten onto the front portion 12. The fastener 54 functions to allow the first and second lateral sections 34 and 36 to be released from the front portion 12 and be refastened onto the front portion 12 multiple times. This means that the wearer can easily remove the absorbent article 10 from his or her body, for example, to go to the toilet, and then refasten the absorbent article 10 about his or her torso. The refastenable mechanism also provides the wearer with the opportunity to release and adjust the absorbent article 10 about their body during use. For example, if the absorbent article 10 appears to be too tight, the wearer can release the first and second lateral sections 34 and 36 from the front portion 12 and then refasten them to loosen the absorbent article 10 against the wearer's body.

Referring to Fig. 1, It should be noted that unlike the hook and loop fasteners 56 and 58, the breakable bonds 46, which secure the first and second lateral sections 34 and 36 together, are designed to be broken only once. The primary function of the breakable

bonds 46 is to join the first and second lateral sections 34 and 36 together during manufacture of the absorbent article 10 and during application of the product as a pull-on article. The absorbent article 10 can be pulled up around the torso of a wearer without breaking the breakable bonds 46. In this case, they will need to be broken before the first and second lateral sections 34 and 36 can be released from the front portion 12.

Returning again to Figs. 1 and 2, the first and second lateral sections 34 and 36 have a length represented by L_1 . The length L_1 is measured parallel to the longitudinal central axis X—X. The length L_1 should be equal to or greater than about 2 inches (about 5 cm). Preferably, for an adult size garment, the length L_1 should range from between about 3 inches to about 7 inches (about 7.6 cm to about 18 cm). Most preferably, for an adult size garment, the length L_1 should range from between about 6 inches to about 7 inches (about 15 cm to about 18 cm). The significance of the dimension L_1 will be explained shortly.

Referring now to Figs. 1 and 3, the absorbent article 10 also includes the back portion 14 that will contact the back portion of a wearer's torso in use. The back portion 14 has first and second side edges 60 and 62, respectively, and first and second ends, 64 and 66 respectively. The back portion 14, as explained above, is depicted as a laminate having an upper layer 22 and a lower layer 24. The upper layer 22, which is closest to the body of the wearer can be liquid permeable or liquid-impermeable. Preferably, the upper layer 22 is liquid permeable. The back portion 14 is divided into a first section 68 and a second section 70. The first section 68 has a length L_2 measured perpendicularly from the first end 64 to a line 72 drawn parallel thereto. The length L_2 should be equal to or greater than about 2 inches (about 5 cm). Preferably, for an adult size garment, the length L_2 should range from between about 3 inches to about 7 inches (about 7.6 cm to about 18 cm). Most preferably, for an adult size garment, the length L_2 should range from between about 6 inches to about 7 inches (about 15 cm to about 18 cm).

The first section 68 can be formed from an elastic material, an elastic composite or it can contain elastic 74. "Stretch bonded laminate" is an elastic material that can be used to form the first section 68. Stretch bonded laminate is manufactured by Kimberly-Clark Corporation having an office at 401 North Lake Street, Neenah, Wisconsin 54956. The elastic 74 can be in the form of elongated elastic strands, ribbons, strips, etc. which extend transversely across the first section 68 from the first side edge 60 to the second side edge 62. Preferably, there are at least six elastic strands 74 contained in the first section 68. The number of elastic strands 74 can vary from two to about fifty. Preferably, the number of elastic strands 74 will range from between about ten to about forty. The

elastic 74 functions to cause the back portion 14 of the absorbent article 10 to securely contact the back torso of the wearer and prevent fluid leakage from occurring at or about the waist opening.

The second section 70 of the back portion 14 has a length L_3 measured
5 perpendicularly from the second end 66 to the line 72 drawn parallel to the first end 64. The length L_3 should be equal to or greater than about 1 inch (about 2.5 cm). Preferably, for an adult size garment, the length L_3 should range from between about 3 inches to about 10 inches (about 8 cm to about 25 cm). Most preferably, for an adult size garment, the length L_3 should range from between about 4 inches to about 8 inches (about 10 cm to
10 about 20 cm).

The second section 70 may or may not contain elastic 74 that extend transversely there across. By designing and manufacturing the absorbent article 10 to have a ratio L_2/L_3 , which ranges from between about 0.1 to about 2, one can improve the body fit of the disposable absorbent article 10. Preferably, the ratio L_2/L_3 ranges from between
15 about 0.2 to about 1.6, and more preferably, the ratio L_2/L_3 ranges from between about 0.3 to about 1.5. By manufacturing the back portion 14 to this desired ratio, one can also minimize fluid leakage.

The second section 70 can have first and second leg elastics 76 and 78 that are aligned adjacent to first and second edges 80 and 82. Preferably, the line 72 will intersect
20 at a point where the first and second edges 80 and 82 meet the first and second edges 60 and 62, respectively. The leg elastics 76 and 78 can include one or more elastic strands, ribbons or strips that are arranged approximately parallel to the first and second edges 80 and 82, respectively. Preferably, there are from between about one to about six elongated elastic strands making up each leg elastic 76 and 78. Most preferably, each of
25 the leg elastics 76 and 78 contains three elastic strands. The elastic strands can be aligned parallel to one another. For good results, the leg elastics 76 and 78 should be positioned inward about 1 inch (about 2.5 cm) from the first and second edges 80 and 82, respectively. More preferably, the leg elastics 76 and 78 should be positioned inward about .75 inches (about 2 cm) from the first and second edges 80 and 82, respectively.
30 Most preferably, the leg elastics 76 and 78 should be positioned inward about .5 inches (about 1.3 cm) from the first and second edges 80 and 82.

The leg elastics 76 and 78 are shown extending from the side edges 60 and 62 of the first section 68 to the second end 66 of the back portion 14. One should note that the exact location of the line 72 would dictate whether the leg elastics 76 and 78 are
35 completely contained within the second section 70 or if they extend into the first section

68. The leg elastics 76 and 78 function to gather the material from which the back portion 14 is formed at a location adjacent to the leg openings. The leg openings are formed as the first and second lateral sections 34 and 36 are secured to the back portion 14 to form a pant-like article. Various types of elastics can be used to form the leg elastics 76 and 78.

- 5 The leg elastics 76 and 78 should have a tension of from between about 10 grams to about 400 grams. Preferably, the leg elastics 76 and 78 should have a tension of from between about 50 grams to about 220 grams. More preferably, the leg elastics 76 and 78 should have a tension of from between about 80 grams to about 200 grams.

- Referring to Figs. 1, 2 and 4, the absorbent article 10 also includes the crotch portion 16. The crotch portion 16 connects the front portion 12 to the back portion 14. As noted above, the front portion 12, back portion 14 and the crotch portion 16 can all be part of a single sheet of material. The crotch portion 16 has a first side edge 84 and a second side edge 86 and can have an hourglass, rectangular, square, oval or some other configuration. Each of the side edges 84 and 86 can be straight and aligned parallel or non-parallel to one another. The side edges 84 and 86 can also be curved, arcuate, irregular, convex or concave in shape. Preferably, the side edges 84 and 86 are arcuate in shape with the narrowest distance between the side edges 84 and 86 occurring along the transverse centerline Y—Y. The crotch portion 16 can be a single layer 18, as depicted, or a laminate. Since the crotch portion 16 acts as a baffle to body fluid that is absorbed by the absorbent article 10, it should be liquid-impermeable. If the crotch portion 16 is a laminate, at least one of the layers forming the laminate should be liquid-impermeable. Polypropylene, polyethylene, or any other thermoplastic material works well as a liquid-impermeable layer. Preferably, the crotch portion 16 is a laminate formed from a layer of thermoplastic film and a layer of non-woven material. The non-woven material can be spunbond. Spunbond is a non-woven material manufactured and commercial sold by Kimberly-Clark Corporation having an office at 401 North Lake Street, Neenah, Wisconsin 54956.

- The crotch portion 16 can also include first and second crotch elastics 88 and 90. The crotch elastics 88 and 90 are located adjacent to the first and second side edges 84 and 86, respectively. The crotch elastics 88 and 90 are preferably contoured to match the profile of the side edges 84 and 86. The crotch elastics 88 and 90 are located inward about 1 inch (about 2.5 cm) of the first and second side edges 84 and 86, respectively. Preferably, the crotch elastics 88 and 90 are located inward about .75 inches (about 2 cm) of the first and second side edges 84 and 86, respectively. More preferably, the crotch

elastics 88 and 90 are located inward about .5 inches (about 1.3 cm) of the first and second side edges 84 and 86, respectively.

The crotch elastics 88 and 90 should have a tension of from between about 10 grams to about 400 grams. Preferably, the crotch elastics 88 and 90 should have a tension of from between about 50 grams to about 220 grams. More preferably, the crotch elastics 88 and 90 should have a tension of from between about 80 grams to about 200 grams.

The crotch elastics 88 and 90 can include one or more elongated elastic strands, ribbons or strips. Preferably, each of said first and second crotch elastics 88 and 90 includes at least two strands of elastics, and more preferably, at least three strands of elastics. The strands of each of the crotch elastics 88 and 90 can be aligned parallel to one another or they can be aligned in a non-parallel relationship, if so desired. A parallel alignment is preferred. The strands of each of the crotch elastics 88 and 90 can be spaced fairly close together, for example, within a millimeter of each other. The exact spacing can be adjusted depending on the size of the article, the width of the crotch portion 16, the strength of the crotch elastics 88 and 90, the material from which the absorbent article 10 is constructed, etc.

Referring to Figs. 3 and 4, the crotch elastics 88 and 90 can be positioned and secured between the layers 22 and 24 forming the laminate, similar to that shown in Fig. 3. Alternatively, the crotch elastics 88 and 90 can be adhered to an upper surface 92 of the upper layer 22 of the laminate, see Fig. 4. Preferably, the first and second crotch elastics 88 and 90 are bonded to the upper surface 92 of the upper layer 22 by an adhesive.

Referring to Figs. 1-4, the absorbent article 10 can include a liquid permeable liner 94. The liquid permeable liner 94 is also referred to as a bodyside cover. The liner 94 is not required, but the absorbent article 10 will be described as including the liner 94. The liquid permeable liner 94, when present, can be formed from any natural or synthetic material that is liquid permeable. The liquid permeable liner 94 can also be formed from a non-woven material. Spunbond is a good material from which to construct the liquid permeable liner 94.

The liquid permeable bodyside liner 94 can be secured to at least one of the front, back or crotch portions 12, 14 or 16. The liquid permeable liner 94 is shown being directly attached to the crotch portion 16 in Fig. 4. Alternatively, the liquid permeable liner 94 can be indirectly attached to the crotch portion 16 via one or more layers. In this case, the intermediate layer would be secured to at least one of the front, back or crotch portions

12, 14 or 16. For example, the liquid permeable liner 94 could be secured to a liquid-impermeable baffle, that is then adhesively secured to the crotch portion 16.

5 In Fig. 1, the periphery of the liquid permeable liner 94 and the periphery of the crotch portion 16 are shown to be coterminous. When the crotch elastics 88 and 90 are positioned on the upper surface 92 of the laminate 20, they can be adhesively secured to the bodyside liner 94 such that they are arranged adjacent to the side edges 84 and 86 of the crotch portion 16.

The absorbent article 10 further includes an absorbent 96 positioned below the liquid permeable liner 94. The absorbent 96 can be in direct contact with the upper layer 48 of the crotch portion 16. The absorbent 96 is designed to absorb body fluid, especially urine and can include one or more layers of absorbent material. The layers can be constructed of similar or different materials. Suitable materials for the absorbent 96 include cellulose, wood pulp fluff, rayon, cotton, and meltblown polymers such as polyester, polypropylene or coform. Coform is a meltblown air-formed combination of meltblown polymers, such as polypropylene, and absorbent staple fibers, such as cellulose. A preferred material is wood pulp fluff, for it is low in cost, relatively easy to form and has great absorbency. It should be noted that if two or more layers are utilized, that it is not necessary that all the layers be formed from the same material or have the same density.

20 The absorbent 96 can also be formed from a composite comprised of a hydrophilic material that can be formed from various natural or synthetic fibers, wood pulp fibers, regenerated cellulose or cotton fibers, or a blend of pulp and other fibers. A preferred material is airlaid tissue.

It is also possible and sometimes advantageous to insert a superabsorbent material into the absorbent 96 so as to increase its ability to absorb a large amount of fluid in relation to its own weight. Typical superabsorbents used in absorbent articles such as incontinence garments and diapers can absorb more than 10 times their weight in body fluid. The superabsorbent material can be inserted as particles, fibers or in sheet form. Hydroxyfunctional polymers have been found to be good superabsorbents for disposable absorbent articles. Such superabsorbents are commercially available from The Dow Chemical Company, Stockhausen, Inc., as well as other companies. Two such superabsorbents are DRYTECH® 2035 M and FAVOR® SXM 880. DRYTECH® is a registered trademark of The Dow Chemical Company having an office at 2030 Dow Center, Midland, Michigan 48642. FAVOR® is a registered trademark of Stockhausen, Inc. having an office at 2401 Doyle Street, Greensboro, North Carolina 27406. The

superabsorbent can be a partially neutralized salt of cross-linked copolymers of polyacrylic acid. Other types of superabsorbent materials known to those skilled in the art can also be used.

Referring now to Figs. 5 and 6, an absorbent assembly 98 is depicted which includes, from top to bottom, a liquid permeable bodyside liner 94, one or more layers of an absorbent 96, one layer being shown, and a liquid-impermeable baffle 100. The liquid-impermeable baffle 100 can be formed from a thin layer of thermoplastic material such as polyethylene, polypropylene or other kinds of liquid-impermeable material. Preferably, the baffle 100 is formed from a liquid-impermeable film. It should be noted that the baffle 100 could be formed from a laminate wherein at least one of the layers is liquid-impermeable.

In the absorbent assembly 98, the crotch elastics 88 and 90 are sandwiched between the liner 94 and the baffle 100. The crotch elastics 88 and 90 can be held in place by a glue, an adhesive, by ultrasonics, by heat, by pressure, by a combination of heat and pressure, or by some other bonding mechanism known to those skilled in the art. It is also possible to secure the crotch elastics 88 and 90 to the lower or exterior surface of the baffle 100 if desired. For good results, the crotch elastics 88 and 90 should be positioned within about 1 inch (about 2.5 cm) from the respective side edge 84 and 86. More preferably, the crotch elastics 88 and 90 should be positioned within about .75 inches (about 2 cm) from the respective side edge 84 and 86. Most preferably, the crotch elastics 88 and 90 should be positioned within about .5 inches (about 1.3 cm) from the respective side edge 84 and 86.

The absorbent assembly 98 can be placed or positioned on or over the crotch portion 16 of the absorbent article 10 and can be retained in place by an adhesive or some other type of fastener. Since the baffle 100 is liquid-impermeable, the crotch portion 16 would not have to be constructed from a liquid-impermeable material. The absorbent assembly 98 can be either permanently or releasably secured to at least one of the front, back or crotch portions 12, 14 or 16 of the absorbent article 10. Preferably, the absorbent assembly 98 is secured to the crotch portion 16 by an adhesive.

Referring now to Figs. 1 and 7, the outer edges 42 and 44 of the first and second lateral sections 34 and 36 are securely attached to the first and second side edges 60 and 62, respectively, of the back portion 14 to form a pant-like article 102. The pant-like article 102 has a waist opening 104 and a pair of first and second leg openings 106 and 108. The leg elastic 76, the crotch elastic 90, and possibly the elastic first section 68 can cooperate to form gathers 110 around the first leg opening 106. Likewise, the leg elastic 78, the crotch elastic 90, and possibly the elastic first section 68 can cooperate to form

gathers 112 around the second leg opening 108. It should be noted that the absorbent article 10 could be sold in either the assembled condition, as is shown in Fig. 7 or with the lateral sections 34 and 36 detached from the front portion 12.

Referring again to Fig. 1, the back portion 14 of the disposable absorbent article 10 has been described with reference to a first section 68 and a second section 70. The first section 68 has a length L_2 and the second section 70 has a length L_3 , both measured parallel to the longitudinal central axis X—X. The combination of the length L_2 and the length L_3 equals a new length L_4 . The length L_4 should range from between about 3 inches (about 7.5 cm) to about 25 inches (about 64 cm). Preferably, for an adult size garment, the length L_4 should range from between about 7 inches to about 17 inches (about 18 cm to about 43 cm). Most preferably, for an adult size garment, the length L_4 should range from between about 10 inches to about 15 inches (about 25 cm to about 38 cm).

In addition, the absorbent article 10 has an overall length L_5 measured perpendicularly from a first end 114 of the first and second lateral sections 34 and 36 to the first end 64 of the back portion 14. The length L_5 should range from between about 10 inches (about 25 cm) to about 45 inches (about 114 cm). Preferably, for an adult size garment, the length L_5 should range from between about 20 inches (about 51 cm) to about 40 inches (about 102 cm). Most preferably, for an adult size garment, the length L_5 should range from between about 30 inches (about 76 cm) to about 35 inches (about 89 cm).

A ratio L_4/L_5 can be established which ranges from between about 0.1 to about 0.5. Preferably, the ratio L_4/L_5 ranges from between about 0.2 to about 0.5 and more preferably, the ratio L_4/L_5 ranges from between about 0.3 to about 0.4. By designing and manufacturing the absorbent article 10 to fit within the values established for the ratio L_4/L_5 , one can be confident that the absorbent article 10 will exhibit improved body fit and be less likely to leak body fluid.

Returning again to the first and second lateral sections 34 and 36, depicted in Fig. 1, it was mentioned that they have a length L_1 . Since the first and second lateral sections 34 and 36 are designed to mate with the back portion 14, it is advantageous to size the length L_1 to be approximately equal to the length L_2 . This will provide an aesthetically pleasing pant-like article 102. However, if one desires, the length L_1 could be sized to be less than, equal to or greater than the length L_2 .

Referring now to Fig. 8, the back portion 14 of the absorbent article 10 is depicted with the elastic 74 removed for clarity of discussion only. The back portion 14, as described above, has a first section 68 and a second section 70. The first section 68 has

a length L_2 that is equal to or greater than about 2 inches (about 5 cm) and the second section 70 has a length L_3 that is equal to or greater than about 1 inch (about 2.5 cm). The second section 70 includes a first area A_1 and a second area A_2 . The first area A_1 is bounded by the second end 66, the line 72 drawn parallel to the first end 64, and the first and second side edges 80 and 82. In essence, the first area A_1 represents the total area of the second section 70. The second area A_2 is depicted as the cross hatched area bounded by first and second lines 116 and 118, the second end 66, and the line 72 drawn parallel to the first end 64. The first and second lines 116 and 118 are drawn perpendicular to the second end 66 at points 120 and 122 where the first and second side edges 80 and 82 intersect the second end 66. The first and second lines 116 and 118 extend vertically upward and intersect the line 72 at points 124 and 126, respectively. It has been found that if one divides the first area A_1 by the second area A_2 , a ratio A_1/A_2 is established. If this ratio A_1/A_2 is maintained within a certain limited range, one can manufacture a disposable absorbent article 10 that exhibits improved body fit in the buttocks region of the wearer. Such improved body fit reduces the likelihood of fluid leakage from occurring which is of utmost importance to a consumer of such products.

The first area A_1 should be equal to or greater than about 175 cm². Preferably, for an adult size garment, the first area A_1 ranges from between about 400 cm² to about 1500 cm². More preferably, for an adult size garment, the first area A_1 ranges from between about 500 cm² to about 1200 cm². Most preferably, for an adult size garment, the first area A_1 ranges from between about 600 cm² to about 1100 cm². The second area A_2 should be equal to or greater than about 50 cm². The ratio A_1/A_2 should range from between about 1.3 to about 3.5. Preferably, the ratio A_1/A_2 should range from between about 1.7 to about 2.5, and more preferably, the ratio A_1/A_2 should range from between about 2.0 to about 2.3.

It should be noted that the first and second lines 116 and 118 are aligned parallel to one another and are spaced apart a distance denoted as W_1 . W_1 represents the width of the second area A_2 . The width W_1 should be equal to or greater than about 4 inches (about 10 cm). Preferably, the width W_1 should range from between about 5 inches (about 13 cm) to about 15 inches (about 38 cm), and more preferably, the width W_1 should range from between about 6 inches (about 15 cm) to about 11 inches (about 28 cm). The dimension W_1 can vary depending upon the type and size of the absorbent article, as well as the age and physical size of the wearer that the absorbent article is designed to be worn by. If the absorbent article is sized to be worn by an infant, the

dimension W_1 will be less than if the absorbent article is designed to be worn by a toddler or by an adult. The gender of the wearer can also affect the dimension W_1 .

Referring to Fig. 9, the back portion 14 and the crotch portion 16 of the absorbent article 10 are depicted with the elastic 74 removed from the back portion 14 for clarity of discussion only. The crotch portion 16 is joined at one end to the second end 66 of the back portion 14. The crotch portion 16 has first and second side edges 84 and 86 and first and second crotch elastics 88 and 90 positioned adjacent to the first and second side edges 84 and 86, respectively. The back portion 14 has a first section 68 and a second section 70. The first section 68 has a length L_2 that is equal to or greater than about 2 inches (about 5 cm) and the second section 70 has a length L_3 that is equal to or greater than about 1 inch (about 2.5 cm). The second section 70 includes a first area A_3 and a second area A_4 . The first area A_3 is bounded by the second end 66, the line 72 drawn parallel to the first end 64, and the first and second side edges 80 and 82. In essence, the first area A_3 represents the total area of the second section 70. The second area A_4 is depicted as the crosshatched area bounded by first and second lines 128 and 130, the second end 66, and the line 72 drawn parallel to the first end 64. The first and second lines 128 and 130 are drawn tangential to the first and second crotch elastics 88 and 90 at points 132 and 134 where the first and second crotch elastics 88 and 90 are spaced closest together. Another way of stating this is that the first and second lines 128 and 130, respectively, are aligned tangentially to the inner most elastic strand of each of the first and second crotch elastics 88 and 90. For a symmetrically shaped article 10, this will occur on the transverse central axis $Y-Y$.

The first and second lines 128 and 130 extend vertically upward toward the first end 64 and intersect both the second end 66 at points 136 and 138, and the line 72 drawn parallel to the first end 64 at points 140 and 142. The crosshatched area bounded by the points 136, 138, 140 and 142 represent the second area A_4 . It has been found that if one divides the first area A_3 by the second area A_4 , that a ratio A_3/A_4 is established. If this ratio A_3/A_4 is maintained within a certain limited range, one can manufacture an absorbent article that exhibits improved body fit in the buttocks region of the wearer. Such improved body fit reduces the likelihood of fluid leakage from occurring which is of utmost importance to a disposable absorbent article.

The first area A_3 should be equal to or greater than about 175 cm^2 . Preferably, the first area A_3 should range from between about 400 cm^2 to about 1500 cm^2 . More preferably, the first area A_3 should range from between about 500 cm^2 to about 1200 cm^2 , and most preferably, the first area A_3 ranges from between about 600 cm^2 to about

1100 cm². The second area A_4 should be equal to or greater than about 35 cm². The ratio A_3/A_4 should range from between about 1.5 to about 5.0. Preferably, the ratio A_3/A_4 should range from between about 2.5 to about 4.0, and more preferably, the ratio A_3/A_4 should range from between about 3.0 to about 3.7.

- 5 It should be noted that the first and second lines 128 and 130 are aligned parallel to one another and are spaced apart a distance denoted as W_2 . W_2 represents the width of the second area A_4 . The width W_2 should be equal to or greater than about 2 inches (about 5 cm). Preferably, the width W_2 should range from between about 3 inches (about 8 cm) to about 7 inches (about 18 cm), and more preferably, the width W_2 should range
- 10 from between about 4 inches (about 10 cm) to about 6 inches (about 15 cm). The dimension W_2 can vary depending upon the type and size of absorbent article, as well as the age and physical size of the wearer that the absorbent article is designed to be worn by. If the absorbent article is sized to be worn by an infant, the dimension W_2 will be less than if the absorbent article is designed to be worn by a toddler or by an adult. The
- 15 gender of the wearer can also affect the dimension W_2 .

- While the invention has been described in conjunction with several specific embodiments, it is to be understood that many alternatives, modifications and variations will be apparent to those skilled in the art in light of the foregoing description. Accordingly, this invention is intended to embrace all such alternatives, modifications and
- 20 variations that fall within the spirit and scope of the appended claims.

We claim:

1. An absorbent article comprising:
 - a) a front portion having a first end, a second end, a first side edge and a second side edge;
 - b) first and second lateral sections releasably attached to said front portion,
5 each of said first and second lateral sections having an outer edge;
 - c) a back portion having a first end, a second end and first and second side edges, said back portion being divided into a first section and a second section, said first section having a length L_2 measured perpendicularly from
10 said first end of said back portion to a line drawn parallel thereto, and said second section having a length L_3 measured perpendicularly from said second end of said back portion to said line drawn parallel to said first end whereby a ratio L_2/L_3 is established which ranges from between about 0.1 to about 2;
 - d) a crotch portion connecting said front portion to said back portion; and
15 e) an absorbent secured to at least one of said front, back or crotch portions, and each of said outer edges of said first and second lateral sections being secured to one of said first and second side edges of said back portion to form a pant-like article having a waist opening and a pair of leg openings.
2. The absorbent article of claim 1 wherein said first and second lateral sections are elastic.
3. The absorbent article of claim 1 wherein said first and second lateral sections overlay said front portion.
4. The absorbent article of claim 1 wherein each of said first and second lateral sections has an inner edge and said pair of inner edges are aligned in an abutting relationship.
5. The absorbent article of claim 4 wherein said pair of inner edges are joined together by breakable bonds.

6. The absorbent article of claim 5 wherein said breakable bonds includes a line of perforations.
7. The absorbent article of claim 1 wherein said back portion includes elastic strands that extend from said first side edge to said second side edge.
8. The absorbent article of claim 1 wherein the dimensions of said lengths L_2 and L_3 equal a length L_4 , and said absorbent article has an overall length L_5 measured from said first end of said front portion to said first end of said back portion, and a ratio L_4/L_5 is established which ranges from between about 0.1 to about 0.5.
9. The absorbent article of claim 8 wherein said ratio L_4/L_5 ranges from between about 0.2 to about 0.5.
10. An absorbent article comprising:
 - a) a front portion having a first end, a second end, a first side edge and a second side edge;
 - b) first and second lateral sections releasably attached to said front portion by hook and loop fasteners, each of said first and second lateral sections having an outer edge;
 - c) a back portion having a first end, a second end and first and second side edges, said back portion being divided into a first section and a second section, said first section having a length L_2 measured perpendicularly from said first end of said back portion to a line drawn parallel thereto, and said second section having a length L_3 measured perpendicularly from said second end of said back portion to said line drawn parallel to said first end whereby a ratio L_2/L_3 is established which ranges from between about 0.1 to about 2;
 - d) a crotch portion connecting said front portion to said back portion;
 - e) a liquid permeable liner secured to at least one of said front, back or crotch portions; and
 - f) an absorbent positioned below said liner, and each of said outer edges of said first and second lateral edges being secured to one of said first and second side edges of said back portion to form a pant-like article having a waist opening and a pair of leg openings.

11. The absorbent article of claim 10 wherein said first and second lateral sections are elastic.
12. The absorbent article of claim 10 wherein said first and second lateral sections overlay said front portion.
13. The absorbent article of claim 10 wherein each of said first and second lateral sections has an inner edge and said pair of inner edges are aligned in an abutting relationship.
14. The absorbent article of claim 10 wherein said pair of inner edges are joined together by breakable bonds.
15. An absorbent article comprising:
- a) a front portion having a first end, a second end, a first side edge and a second side;
 - b) first and second lateral sections releasably attached to said front portion, each of said first and second lateral sections having an outer edge;
 - c) a back portion having a first end, a second end and first and second side edges, said back portion being divided into a first section and a second section, said first section having a length L_2 measured perpendicularly from said first end of said back portion to a line drawn parallel thereto, and said second section having a length L_3 measured perpendicularly from said second end of said back portion to said line drawn parallel to said first end whereby a ratio L_2/L_3 is established which ranges from between about 0.1 to about 2;
 - d) a crotch portion connecting said front portion to said back portion;
 - e) a liquid permeable liner secured to at least one of said front, back or crotch portions; and
 - f) an absorbent positioned below said liner, and each of said outer edges of said first and second lateral edges being secured to one of said first and second side edges of said back portion to form a pant-like article having a waist opening and a pair of leg openings, wherein said lengths L_2 and L_3 equal a length L_4 and said absorbent article has an overall length L_5

measured from said first end of said front portion to said first end of said back portion, and a ratio L_4/L_3 is established which ranges from between about 0.2 to about 0.5.

16. The absorbent article of claim 15 wherein said first and second lateral sections are releasably attached to said front portion by hook and loop fasteners.
17. The absorbent article of claim 16 wherein said front portion contains said hook fasteners.
18. The absorbent article of claim 16 said front portion contains said loop fasteners.
19. The absorbent article of claim 15 wherein each of said first and second lateral sections has an inner edge and said pair of inner edges are aligned in an abutting relationship.
20. The absorbent article of claim 15 wherein said pair of inner edges are joined together by breakable bonds.




FIG. 1




FIG. 2

2/4




FIG. 3




FIG. 4




FIG. 5




FIG. 6

3/4




FIG. 7

4/4




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

Intern. Patent Application No.

PCT/US 00/23077

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F13/15

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 36566 A (PROCTER & GAMBLE) 9 October 1997 (1997-10-09) the whole document ---	1-3, 7-12,15, 16
X	GB 2 288 313 A (MOELNLYCKE AB) 18 October 1995 (1995-10-18) claims 5,10,15; figures ---	1,2, 7-11,15, 16
X	GB 2 308 290 A (MOELNLYCKE AB) 25 June 1997 (1997-06-25) claims; figures ---	1,2,4-7, 10,11, 14-16
A	WO 95 00096 A (PROCTER & GAMBLE) 5 January 1995 (1995-01-05) abstract; figures ---	4,5,13, 14,19,20
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

A document member of the same patent family

Date of the actual completion of the international search

14 November 2000

Date of mailing of the international search report

27/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mirza, A

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/23077

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 294 865 A (MOELNLYCKE AB) 15 May 1996 (1996-05-15) abstract; figures	1-20

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 00/23077

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9736566 A	09-10-1997	US 5897545 A	27-04-1999
		AU 2334797 A	22-10-1997
		BR 9708519 A	03-08-1999
		CA 2251694 A	09-10-1997
		EP 0959855 A	01-12-1999
		JP 11507286 T	29-06-1999
		US 5957908 A	28-09-1999
GB 2288313 A	18-10-1995	SE 508613 C	19-10-1998
		AU 696255 B	03-09-1998
		AU 2271395 A	30-10-1995
		CA 2187021 A	19-10-1995
		CN 1146145 A	26-03-1997
		CZ 9602994 A	12-02-1997
		EP 0755237 A	29-01-1997
		FI 964085 A	11-10-1996
		HU 77677 A	28-07-1998
		IL 112986 A	14-07-1999
		JP 9511426 T	18-11-1997
		NO 964283 A	09-10-1996
		NZ 284182 A	19-12-1997
		PL 316681 A	03-02-1997
		SE 9401226 A	13-10-1995
		WO 9527461 A	19-10-1995
		SK 130996 A	06-08-1997
		US 5855574 A	05-01-1999
		ZA 9502490 A	15-12-1995
GB 2308290 A	25-06-1997	SE 508214 C	14-09-1998
		AU 708093 B	29-07-1999
		AU 1215397 A	17-07-1997
		BR 9612229 A	13-07-1999
		CZ 9801818 A	11-11-1998
		EP 0959837 A	01-12-1999
		HU 9901548 A	28-09-1999
		NZ 324878 A	29-06-1999
		PL 327342 A	07-12-1998
		SE 9504613 A	23-06-1997
		WO 9723180 A	03-07-1997
		SK 69698 A	04-11-1998
WO 9500096 A	05-01-1995	AU 7059994 A	17-01-1995
		CA 2165288 A	05-01-1995
		DE 69418713 D	01-07-1999
		DE 69418713 T	11-11-1999
		EP 0705088 A	10-04-1996
		ES 2131691 T	01-08-1999
		JP 8511709 T	10-12-1996
		US 5624420 A	29-04-1997
GB 2294865 A	15-05-1996	SE 509063 C	30-11-1998
		AU 697312 B	01-10-1998
		AU 3885595 A	31-05-1996
		DE 69518854 D	19-10-2000
		EP 0790816 A	27-08-1997
		JP 10508519 T	25-08-1998
		NZ 295501 A	24-09-1998
		PL 319950 A	01-09-1997

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 00/23077

Patent document cited in search report	Publication date	Patent family member(s)	Publication date:
GB 2294865 A		SE 9403832 A	09-05-1996
		WO 9614039 A	17-05-1996
		SK 52597 A	08-10-1997
		TR 960392 A	21-06-1996
		ZA 9509387 A	28-05-1996